



VDSL / ADSL N300 WiFi Gateway with VoIP




Perfect for

- VDSL and ADSL service providers
- Connecting to your fixed line DSL service
- Connecting to a Fibre / NBN service through the Ethernet WAN port
- Creating a storage network to share files saved on a hard drive with all connected users

KEY FEATURES

- ⌚ Fully featured VDSL2 / ADSL2+ Gateway
- ⌚ 1 x 10/100/1000 Gigabit Ethernet WAN port for connection to fibre services
- ⌚ 4 x 10/100 Ethernet LAN ports for multiple wired connections
- ⌚ Wireless N300 Access Point for multiple high speed WiFi connections
- ⌚ 2 x FXS ports for connecting a telephone to make VoIP calls
- ⌚ 2 x USB host ports – supports USB storage device for file sharing
- ⌚ Built-in media server. Just add a USB hard drive
- ⌚ NBN ready: carefully developed hardware and software features to ensure this device is optimised for use on the National Broadband Network:
 - Wireline Routing Speeds
 - IGMP Snooping
 - IPTV IGMP V1 V2 Pass through
 - QoS
- ⌚ IPv6 ready for the next generation IP addressing
- ⌚ WPS button for simple setup of your wireless network





SPECIFICATIONS

PACKAGE INCLUDES

- NetComm Wireless VDSL/ADSL N300 WiFi Modem Router with Voice
- Power Adapter
- Printed Quick Start Guide
- Ethernet Cable (RJ-45)
- Phone Cable (RJ-11)
- Wireless Security Card
- Warranty Card

ENVIRONMENTAL AND PHYSICAL

- Operating temperature: 0-40°C, Humidity: 10%-95% non-condensing
- Storage temperature: -20-70°C, Humidity: 5%-95% non-condensing
- DC Input Voltage 12W/1.5A
- Dimensions: 190(W) x 146 (H) x 54 (D) mm
- Weight: 326 grams

DEVICE INTERFACE

- 1 x RJ45 10/100/1000Mbps WAN port
- 1 x RJ11 ADSL/VDSL port
- 4 x RJ45 10/100Mbps LAN ports
- 2 x FXS ports
- 2 x USB 2.0 Ports (storage)
- 1 x Reset button
- 1 x WPS button
- 1 x WLAN button
- 1 x Power jack
- 1 x Power switch
- LED (Power/DSL/Internet/WAN/LAN1-4/WLAN/WPS/USB1/USB2/Phone1/Phone2)

VDSL FEATURES

- ITU-T G.993.2 VDSL2
- Support 8a, 8b, 12a, 12b, 17a profile
- Support G.vector
- Support ATM and PTM
- Support G.INP

ADSL2+

- ITU 992.1 (G.dmt) Annex A,
- ITU 992.2 (G.lite),
- ITU 992.3 ADSL2 (G.dmt.bis),
- ITU 992.5 ADSL2+
- Annex L / Annex M
- Support multiple PVCs

ETHERNET WAN

- PPPoE, DHCP client, Static IP

WIRELESS

- IEEE 802.11n. Backwards compatible with IEEE 802.11b/g
- 2.4GHz WiFi
- SSID broadcast or in stealth mode
- Auto/Manual Channel selection
- WEP/WPA/WPA-PSK/WPA2/WPA2-PSK
- WPS button (WiFi Protected Setup)

VOIP

PROTOCOL

- o SIP 2.0

VOICE/FAX

- o G.711 and G.723, G.726
- o FAX: T.38 FAX Relay

NAS

- File sharing

SECURITY

- Firewall
- MAC filtering

ROUTING

- Static Route
- Dynamic Route (RIP v1/v2)
- Supports Layer 2 Bridge Mode
- DMZ


ADMINISTRATION

- QoS
- SNMP
- UPnP
- Syslog
- Web-based UI
- Remote Login
- TR-069 Auto provisioning
- Backup/Restore Settings

COMPLIANCE

- RCM, NZ Telepermit

VDSL / ADSL N300 WiFi Gateway with VoIP



Featuring a VDSL2/ADSL2+ modem and an Ethernet WAN port, you can choose whether you connect to the Internet via DSL or a fibre service. Internet services are still predominantly delivered into Australian homes largely using ADSL and Australia's NBN will use different technologies. Australia's NBN will be largely delivered with two methods; Fibre to the Node (FTTN) and Fibre to the Premises (FTTP). The majority of connections will be FTTN which will use VDSL technology to deliver high speeds into buildings. FTTP will provide fast speeds (up to 100Mbps) and users will need an Ethernet WAN port to access this service.

This router also includes 2 x USB host ports that can be used to connect USB devices so that their capabilities can be shared with all connected users. Connect a USB hard drive so that all files stored can be accessed and shared.

All of these features can be shared with multiple users via the built-in WiFi access point or the four LAN Ethernet ports. The high speed WiFi N provides a signal strong enough to penetrate the far corners of a house and can connect all WiFi enabled devices, such as laptops, smart phones, gaming consoles, tablets and PCs. The four LAN Ethernet ports provide a wired connection that can be used to connect desktop computers, media devices or any Ethernet equipped product.

- 1 Maximum wireless signal rate and coverage values are derived from IEEE Standard 802.11g and 802.11n specifications. Actual wireless speed and coverage are dependent on network and environmental conditions included but not limited to volume of network traffic, building materials and construction/layout.



NetCommWireless

NETCOMM WIRELESS LIMITED

Head Office - 18-20 Orion Road, Lane Cove,
NSW 2066, Sydney, Australia ABN 85 002 490 486

E: sales@netcommwireless.com

www.netcommwireless.com