Microsoft LX-3000

Digital USB Stereo Headset | Noise-Canceling Microphone



Version Information	
Product Name	Microsoft [®] LifeChat LX-3000
Product Version	Microsoft LifeChat LX-3000
Headset Version	Microsoft LifeChat LX-3000
Product Dimensions	
Headset Length	7.04 inches (178 millimeters)
Headset Width	6.38 inches (162 millimeters)
Headset Depth/Height	3.11 inches (78.9 millimeters)
Headset Weight	8.32 ounces (236 grams)
Headset Cable Length	72.0 inches +6/-0 inches (1829 millimeters +152/-0 millimeters)
Compatibility and Localization	
Interface	High-speed USB compatible with the USB 2.0 specification
Operating Systems	Microsoft Windows® 7, Windows Vista®, and Windows XP with Service Pack 2 (excluding Windows XP 64-bit)
Top-line System Requirements	Requires a PC that meets the requirements for and has installed one of these operating systems:
Top-line System Requirements	Microsoft Windows 7, Windows Vista, or Windows XP with Service Pack 2 (excluding Windows XP 64-bit)
	Pentium II 550 MHz (Pentium IV 1.4 GHz recommended) or higher
	• 60 MB hard drive space
	• USB port 1.1 (USB 2.0 recommended)
	You must accept License Terms for software download. Please download the latest available software version for your OS/Hardware combination.
	rou must accept License Terms for software download. Please download the latest available software version for your OS/hardware combination.
	Internet access may be required for certain features. Local and/or long-distance telephone toll charges may apply.
	Software download required for full functionality of all features.
Compatibility Logos	Certified for Microsoft Windows XP Certified for Microsoft Windows XP
Compatibility Logos	- Certified USB logo
Product Feature Performance	* Octanica dob logo
Headset Features	Digital USB
neauset reatures	Built-in unidirectional microphone with acoustic noise cancellation
	• In-line volume controls
	Pivoting boom microphone with 180-degree movement
	• Windows Live™ Call Button
Windows Live Integration Features	Audio Chat Features: Windows Live Call button delivers one touch access to voice calls and enables automatic audio switching from music to your audio
	call*
Call Button Life	10,000 actuations
Storage Temperature & Humidity	-40 F (-40 °C) to 140 °F (60 °C) with 65% relative humidity (non-condensing)
Operating Temperature & Humidity	32° F (0° C) to 104° F (40° C) with 80% relative humidity (non-condensing)
Certification Information	
Country of Manufacture	People's Republic of China
ISO 9001 Qualified Manufacturer	Yes
ISO 14001 Qualified Manufacturer	Yes
Restriction on Hazardous Substances	This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction of
Trocking of Trazaradus Gasetanose	the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals
	(REACH) regulation regarding Substances of Very High Concern.
FCC ID	This device complies with Part 15 of the FCC Rules and Industry Canada ICES-003. Operation is subject to the following two conditions: (1) This device
	may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired
	operation. Tested to comply with FCC standards. For home and office use. Model number: 1084, LifeChat LX-3000.
Agency and Regulatory Marks	• ICES-003 report on file (Canada)
	EIP Pollution Control Mark, EPUP (China)
	CE Declaration of Conformity, Safety and EMC (European Union)
	WEEE (European Union)
	VCCI Certificate (Japan)
	• MIC Certificate (Korea)
	GOST Certificate (Russia)
	CITC Letter (Kingdom of Saudi Arabia)
	• FCC Declaration of Conformity (USA)
	• UL and cUL Listed Accessory (USA and Canada)
	CB Scheme Certificate (International)
Windows Hardware Quality Labs (WHQL)	ID: 1332667 Microsoft Windows 7